

TUDELÜ SYSTEM BENEFITS

■ SECURITY AND PRIVACY

Retractable walls provide superior sound insulation, ensuring that confidential discussions, meetings, and operations are shielded from eavesdropping or external distractions. This is essential for government offices handling sensitive information.

DURABILITY AND COMPLIANCE

Government environments demand robust, long-lasting products that can handle frequent use. Retractable walls are constructed from durable materials to ensure longevity in high-traffic areas, government offices, or public spaces.

SPACE FLEXIBILITY

Government buildings often need to adapt to different functions, such as transforming a large conference room into smaller meeting spaces, or creating open spaces for events and hearings. Retractable walls allow for easy, on-the-fly reconfiguration to meet the changing demands of the space.

OUR SERVICES



AMERICAN

Engineering, design, and manufacture all done in the USA



MOTORIZED

100% remote controlled for zero manual effort



COMPACT

Full system has tiny footprint in ceiling, starting from 10" x 10"



INSTALLABLE

Easy install for new construction and retrofitting



Tudelü_®



Key Benefits of the Tudelü Systems

Customizable Sizes of up to 20ft wide x 10ft tall

36 - 48 True STC sound barrier for effective sound reduction. This is the same noise reduction as traditional dry wall.

Easy Installation, either through Tudelü direct or through our step-by-step instructions.

100% Motorized - anyone can operate this product with a simple press of a button.

Durable Material - including powder coated extruded aluminum.

Patented Technology - including Stable Griprail Technology.

Compact Footprint - featuring inset design options, meaning ZERO eye sores.

Seamless Design - No matter your dimensions, Tudelü walls won't hurt your aesthetic.

Built-in Safety - auto open feature when the system feels the slightest resistance, so you and your futniture are both safe.

Easy Maintenance - simple soap and water will keep your system looking new for years to come.

Technical Information	Closure	Private	Secluded	Mute
STC of System	-	36	38	48
OTC of System	-	22	30	30
Max Height in feet	10'	10'	12'	15'
Max Width in feet	20'	20'	20'	40'
Wall Thickness in inches	2"	4"	4"	4"
Weight of Wall Fabric in lbs. (per sq. ft)	2"	4"	4"	4"
Available Fabric Choices	Various	Various	Various	Various
Framing Color	White	White	White	White
Housing Dimensions in Inches	10' x 10'	22' x 10'	22' x 10'	14' x 26'
Power Requirements	120V	120V	120V	120V
Safety Features				
Infrared Sensor				
Back Up Operation When Sensor	Ø	⊘	⊘	⊘
Triggered				
Additional Features				
Smart Device Integration				
Modular Design for Auto-Leveling			⊘	⊘
Sealed Border			Ø	
Tight Stretch Magnets	⊘	⊘	⊘	⊘
Product Finishing	Single Sided	Dual Sided	Dual Sided	Dual Sided
Quiet Open	Ø	⊘	⊘	⊘
1 Touch Remote Controlled	Ø	Ø	Ø	Ø
Patented GripRail Technology	Ø	⊘	⊘	⊘
Modular Delivery		Ø		
Smart Device Integration	Ø	⊘	⊘	⊘



