

TUDELÜ SYSTEM BENEFITS

■ PRIVACY AND ACOUSTIC PERFORMANCE

Retractable walls in healthcare settings offer excellent sound insulation, ensuring patient confidentiality and reducing noise from surrounding areas. This is crucial in environments such as hospital rooms, treatment areas, or consultation rooms, where privacy is essential.

HYGIENE AND EASY MAINTENANCE

Healthcare environments require walls that can be cleaned and disinfected frequently. Retractable walls are often designed with smooth, durable materials that prevent the buildup of dirt, germs, or bacteria and can be easily wiped down.

SPACE FLEXIBILITY

Retractable walls allow healthcare spaces to be easily reconfigured for different needs, such as converting a large room into smaller private consultation areas, or creating additional space for emergencies.

OUR SERVICES



AMERICAN

Engineering, design, and manufacture all done in the USA



MOTORIZED

100% remote controlled for zero manual effort



COMPACT

Full system has tiny footprint in ceiling, starting from 10" x 10"



INSTALLABLE

Easy install for new construction and retrofitting



🗜 Tudelü.



Key Benefits of the Tudelü Systems

Customizable Sizes of up to 20ft wide x 10ft tall

36 - 48 True STC sound barrier for effective sound reduction. This is the same noise reduction as traditional dry wall.

Easy Installation, either through Tudelü direct or through our step-by-step instructions.

100% Motorized - anyone can operate this product with a simple press of a button.

Durable Material - including powder coated extruded aluminum.

Patented Technology - including Stable Griprail Technology.

Compact Footprint - featuring inset design options, meaning ZERO eye sores.

Seamless Design - No matter your dimensions, Tudelü walls won't hurt your aesthetic.

Built-in Safety - auto open feature when the system feels the slightest resistance, so you and your futniture are both safe.

Easy Maintenance - simple soap and water will keep your system looking new for years to come.

Technical Information	Closure	Private	Secluded	Mute
STC of System	-	36	38	48
OTC of System	-	22	30	30
Max Height in feet	10'	10'	12'	15'
Max Width in feet	20'	20'	20'	40'
Wall Thickness in inches	2"	4"	4"	4"
Weight of Wall Fabric in lbs. (per sq. ft)	2"	4"	4"	4"
Available Fabric Choices	Various	Various	Various	Various
Framing Color	White	White	White	White
Housing Dimensions in Inches	10' x 10'	22' x 10'	22' x 10'	14' x 26'
Power Requirements	120V	120V	120V	120V
Safety Features				
Infrared Sensor				
Back Up Operation When Sensor				✓
Triggered				
Additional Features				
Smart Device Integration				
Modular Design for Auto-Leveling	⊘		⊘	✓
Sealed Border				
Tight Stretch Magnets			⊘	⊘
Product Finishing	Single Sided	Dual Sided	Dual Sided	Dual Sided
Quiet Open	⊘		⊘	⊘
1 Touch Remote Controlled	Ø		Ø	Ø
Patented GripRail Technology	✓		⊘	⊘
Modular Delivery				
Smart Device Integration	Ø		⊘	⊘



